

Holux™ GPSmile 62E Car Navigator



- 135(W) x 86(H) x 12.9(D) mm /196.2g weight
- Flat Screen Design
- 5" WQVGA TFT LCD
- Multi-Language support
- TMC (optional)

Specifications

Hardware

- Display :
5" WQVGA TFT LCD with touch screen
Brightness : 250nits
Resolution : 480 x 272 pixels
Contrast/Back light : adjustable
- On board Button/Keys :
on/off + sleep/wake up button, reset hole
- Sound System :
1w 8ohm built-in speaker
- Memory :
Internal Memory-RAM : SDRAM 64MB
Internal Memory-ROM : 64MB Nand
Flash(standard), support up to 4GB
- GPS Features :
Built-in Patch Antenna.
GPS info.
 - Tracking sensitivity: -159dBm
 - Tracking:L1,C/A code
 - Channels:20 parallel channels
 - Reacquisition: 0.1 sec (avg.)
 - Hot Start: <3 sec. (avg.)
 - Warm Start: <38 sec. (avg.)
 - Cold Start: <43 sec. (avg.)
 - Position Accuracy: within 10m
 - Max. update Rate: 1Hz
 - Velocity: 0.1 m/sec.(max)
 - WAAS: available(Above GPS chip data follow original spec.)
- Temperature :
Operation : -10°C to 50°C
Storage : -20°C to 60°C

Audio :

- Software volume control
- Built-in Speaker 1W, 8 ohm

Connection

- USB : USB 1.1 Client
- Expansion : Micro SD™, Support 4GB(Max.)
- Battery : Built-in 1450mAh Li-Poly battery
- Recharge through USB Jack

Software

- Windows™ CE 5.0 core
- Firmware upgrade :
Flash Eprom filed programming software available
- Time Mark :
output 1 pulse/sec, aligned with GPS time ±1u sec
Photo & Text Viewer

Accessories

- Car Charger
- Cradle/Gooseneck
- USB cable
- User manual, Quick Guide
- Micro SD Card